Chrosziel
...for optical excellence

QuickLock®© tripod adapter and bridge plates.

QuickLock, for many cameras – the solid connection to the tripod.

Special version
401-122

For all bridge plates: The various offsets of the optical axes can be compensated for by using the slotted holes. (e.g. Sony left; Thomson centre; Panasonic right).

The patented QuickLock tripod adapter plate: for quick and easy, play-free camera connection

Suitable for all cameras which are equipped with wedge plate connections (V-mount) in the front and a mounting bracket behind the shoulder support.
The Chrosziel QuickLock plate clamps the camera automatically and easily, and even after decades of use, still works perfectly thanks to its patented mechanics: pressure on the wedge plate and traction on the camera‘s mounting bracket. It protects against unintentional opening, but the camera can still be quickly and easily removed in a flowing movement. On the bottom, two slot nuts with a 1/4 and 3/8 inch thread slide over a large area to fix onto a tripod or the bridge plates.

In combination with the **bridge plates,** adjustment to the centre of gravity on the tripod is very easy. The plates come with 19 mm stainless steel rods (video standard). All accessories for the 15mm light-weight supports fit by means of an adaptor. For video cameras with different optical axes, bridge plates are specially adapted.
For the use of film accessories on video cameras, a special version adjusts optical axes. This version is based on 15mm stainless steel rods.

Components:	Article no.
QuickLock tripod adapter plate	401-130
Bridge plate 19mm Video-Standard (rod ∅ 19 mm, rod centre to centre spacing 105 mm)	401-121
Bridge plate 19mm Video-Standard for Sony HDC 1500	401-123
Bridge plate 19mm Video-Standard for Sony F23 / 35	401-F235
QuickLock kit for Sony F 23 / 35	401-F231
QuickLock shoulder support kit for Sony F23 / 35	401-F240
Universal Accessory Mount for Sony F23 / 35	401-F234
QuickLock Adapter Kit for RED One	401-RED1
Bridge plate 19mm for RED One	401-124
Bridge plate 19mm Video-Standard for SI-2K	401-SI2K
Bridge plate with integrated QuickLock connection for film accessories on video cameras (rod ∅ 15 mm, rod centre-to-centre spacing 100 mm)	401-122