

.H



Key Features

- Patent Pending Ultra-Adjustable Design!
- 10.4" reversing LCD display
- Designed for MiniDV/HD cameras
- Readable to 12 feet
- Complete with FREE PC AND Mac software
- FREE PowerPoint prompting software
- VGA and composite inputs
- Run on 100-240V AC or 12v DC
- Adjustable mirror height/angle adjustment
- Perfect balance with any size camera
- Premium HD 60/40 Ultra Clear
- Rear anti reflection coating reduces
- Folds flat for safe, compact transport
- Completely tool-less setup
- Modular system design allows for quick change to larger/smaller LCD/Mirror
- Lightweight –use with tripod or handheld
- Lightweight aluminum extrusion frames
- Easy top side camera adjustment
- 3 year warranty on hardware

THE HARDWARE

The ProLine 11 offers innovative, patent pending features unavailable on any other teleprompter. It's completely tool-less design offers quick setup and breakdown with any size camera. Our patent pending mirror assembly offers both height AND angle adjustment for perfect camera centering and presenter viewing angle. The mirror assembly also folds flat for fast, safe transport. The use of custom aluminum extrusions (instead of heavy slab aluminum) combined with our ultra light LCD panels make the ProLine 11 the lightest prompters in their class. The lightweight design eliminates the need for costly, heavy-duty tripods and offers significantly improved panning and tilt performance.

Need a free standing prompter also? Free-standing prompters don't require mounting the camera on the teleprompter. With our Free Stand kit you can convert your ProLine 11 in just minutes to a free-standing style teleprompter. To use just slide your camera on your existing tripod behind the prompter. Comes complete with two stands for seated and standing positions. Click here for a description of our ProLine Free Stand prompter.

THE GLASS

Today's high definition cameras demand equally high performance optics. The All models utilize exclusive UltraClear HD beamsplitter glass that uses ultra pure, low iron glass that eliminates the color shift and light loss found in many competitive products. To further improve performance we add an anti-reflection coating on the back of the glass to virtually eliminate reflections that can bounce back into the lens. For situations with high ambient light such as direct sunlight we offer a "High Bright" glass that offers 25% brighter viewing for the talent. We also offer our exclusive unbreakable acrylic beamsplitter for use in shock prone applications.

THE SOFTWARE

The ProLine 11 offers the best software package FREE with each system. Included is both PC AND native Mac versions for our industry leading Flip-Q teleprompter software. International customers will appreciate the Unicode support that supports any standard font as well as right to left reading languages. You can also choose to view Flip-Q in nine different languages so all screen buttons and help files are in your native language.

This complete software bundle is shipped on a USB Flash drive and includes FREE lifetime upgrade support. To upgrade just plug in the USB drive, connect to the Internet and click "Upgrade". To prompt simply plug in the USB flash drive into any PC or Mac and start prompting

THE LCD

The ProLine 11 standard LCD panels are the lightest weight, lowest profile designs in their class. In addition, they offer both VGA and composite video inputs adaptable with any computer output or application. They also offer flexible power options including 100-240V AC or external 12v DC input for use in the field without AC.

Need a larger prompter? Just purchase our Broadcast kit to convert your ProLine 11 to an ultra compact 10.4" prompter. Just slide off the existing 10.4" LCD and mirror assembly and slide on the 15" or 17" LCD and mirror – takes just two minutes!

Included Items

- All mounting hardware
- Riser for use with smaller cameras
- 60/40 Ultra clear beamsplitter mirror
- Flip-Q Pro teleprompter software for PC and Mac
- PowerFlip – reversing PowerPoint software
- USB Flash drive for system software
- 25 foot VGA extension cable
- 3 year warranty

Options

Wireless remote Control - (PC Only)

Gives complete control over scroll speed/direction, stop/start, and selecting cue points within 50 feet.

Wired Remote Control -

Soft Case -

Hard Case

Acrylic Beamsplitter Option -

VGA Distribution Amplifier -

Allows up to four VGA monitors to be run from one VGA output. Amplifies signal for runs up to 200 feet.

Specifications

General

- Weight: 9.9 pounds
- Dimensions – Folded for Transport: 17" x 10" x 10"
- 6061 aluminum components
- All aluminum black anodized
- Includes dual height riser necessary for smaller cameras

Beamsplitter

- Beamsplitter Material: Low Iron,
- Ultra Clear Glass 1/8" thick
- Mirror Size: 10"x10"
- Coating: Front - 60/40 beamsplitter, back - anti-reflection coating
- Options: 50/50 hi-bright or unbreakable acrylic options

LCD Display

- 10.4" reversing LCD TFT color LCD
- Built in speakers
- Controls
- Screen Size: 15"/17" 4:3 format.
- Weight: 4.1 pounds/6.6 pounds
- Inputs: VGA, Composite Video
- Power: 12v DC, 100-240v AC adapter included
- Resolution: Up to 1024x768
- Refresh rate: up to 60hz